

Customer Display 8035

Soludisplay's 8035 multi language LCD customer display is an excellent tool for transmitting transactions, AD message, and customer greeting at POS system. The bright alphanumeric LCD display provides wide viewing angles, no matter in close or short distance. 8035 LCD customer display also support multi languages (English / Japan, English/ Europe, English/Russia), let it application of multi lingual environments. With ESC/POS command codes, 8035 can work under any operation system and platform.

Features

- Easy to read of blue background & white characters display.
- Six adjustable viewing angles and visual swivel design
- Multi language support: English / Japan, English / Europe, English/Russia
- USB/RS232 communication
- Built-in and ESC/POS command codes
- OPOS (OLE for retail POS) Competable

Innovate with Technology

Win customers with service

Specifications

8035 Specifications:

Display:

- Type: Alphanumeric dot matrix liquid crystal display
- Text mode: 20 Characters X 2 lines
- Character size: 5mm(w) x 10mm (H) ,5x7 dot
- Display color: Blue (back color) and: White (character color)
- Brightness: 600 cd/m²
- Adjustable angle: 360° swivels and 45 tilt (6-position)

Interface:

- USB 2.0 user access 8035 via virtual Comport
- RS-232 with DC jack

Software Programming:

- Command ESC/POS ,Ultimate mode, OPOS (OLE for Retail POS)
- Multi Language: English / Japan
English / Europe
English / Russia

Power Requirement:

- 5V DC from HOST USB port
- 12V DC from RS232 port

Physical:

- Display panel dimensions: 214 (L) x 70 (W) x 40 (H)mm
- Pole height: 140mm or 280mm
- Weight: 950 g
- Material: ABS plastic
- Colors: Dark Gray or White
- Bottom Plate Material: ABS plastic with metal place