



**this touchscreen is the perfect choice for placement on table-tops. A foldable foot supports the monitor in the back. It can be adjusted to different heights, so it is possible to use it upright, like a normal monitor or almost horizontal to operate and view it from above. The orientation of the pictures does not have to be rotated in this case. The light-intensive LCD display is easy to read even under difficult lighting conditions or from unfavourable angles.**

The integrated touchscreen registers signals on its touch-sensitive surface and automatically transforms them into mouse signals. Simply connect the monitor to the USB port of the computer. Any software can be used with this touchscreen without the need of adjustments or driver installation.

To setup the monitor, it features an intelligent on-screen-display that allows adjustments from the front panel conveniently and menu-driven.

Specifications	
<b>Display Features</b>	
<b>Screen</b>	15 inch TFT LCD
<b>Power Input</b>	AC 90~264 V, 50~60 Hz.
<b>Display Area</b>	304x228 mm (HxV)
<b>Contrast Ratio</b>	300:1
<b>Pixel Pitch</b>	0.297x0.297 mm (HxV)
<b>View Angle</b>	R/L +60°~-60° U/D +55°~-65°
<b>Resolution</b>	XGA 1024x768 75 Hz (max.)
<b>Operation Features</b>	
<b>Brightness</b>	250 cd/m <sup>2</sup>
<b>Response Time</b>	Tf/Tf=15/10ms
<b>Interface</b>	Analog RGB
<b>Connectors</b>	R/L Audio, 15-pin-D-SUB
<b>User's Control</b>	
<b>Front Panel Controls</b>	Auto Adjust, Menu, up, down, Select+/-, ESC, Volume
<b>Physical Specification</b>	
<b>Dimensions</b>	360x360x180 mm (HxWxD)
<b>Net Weight</b>	4.6 kg
<b>Power</b>	
<b>Power Saving</b>	VESA DPMS Standard
<b>Power Consumption</b>	30W (Typ.)
<b>Resistive Touch Panel</b>	
<b>Input Mode</b>	Stylus Pen or Finger
<b>Operation Temp.</b>	-10°C~70°C
<b>Hardness</b>	3H
<b>Transparency</b>	>80%
<b>Controller Type</b>	USB

